

## **MITA DC-162**

### **PRODUCT STRENGTHS**

Oversize Capability up to 11 x 17  
Dual Paper Cassette Flexibility  
Interrupt Function  
Stationary Platen

### **PRODUCT LIMITATIONS**

Variable Exposure Dial  
Requires Experimentation To Attain  
Acceptable Copy Quality  
Requires Fuser Oil

<b>COMPANY:</b>	MITA
<b>MODEL:</b>	DC-162
<b>SUGGESTED RETAIL PRICE:</b>	\$4,995
<b>RENTAL PRICING:</b>	Dealer Option
<b>MAINTENANCE CONTRACT (Purchased Units Only):</b>	Dealer Option

**TOSHIBA AMERICA**

# Competitive Product Guide

## MITA DC-162

Copier Type:	TT
Platen:	Stationary Flatbed
Segment:	2
Warm Up Time:	4 min.
First/Multi Time:	5 sec., 15 c/m
Photoconductor Type:	Selenium Drum
Exposure Method:	Halogen Lamp
Development Method:	Dry Toner
Drum Cleaning System:	Magnetic Brush
Image Fusing System:	Heat and Pressure
Paper Supply:	Dual Cassettes Sheet-Fed
Manual Sheet-Bypass:	None
Capacity:	250 Sheets/Cassette
Paper Size Selector:	Touch
Min/Max Copy Sizes:	5½ × 8½ 11 × 17
Multi-Copy:	Digital, 1-99, Auto Reset (after 2 min.)
Exposure Control:	Light/Dark Slide
Toner Density:	Automatic
Print, Stop Print:	Yes
Other:	None
Paper Supply Indicator:	Indicator (int'l symbol)
Toner Supply Indicator:	Add Toner Light
Number Copies Made/ Remaining:	Digital Countdown
Paper Jam/Other Problems:	Jam Detection (by location)
Other:	Interrupt
Mfr.'s Recommended Monthly Volume:	0 to 15,000
Dimensions (H × W × D):	21 × 31½ × 21¾
Weight:	260 lbs
Power Consumption:	115V, 60Hz, 12A

# TOSHIBA AMERICA