PITNEY BOWES 5200

PRODUCT STRENGTHS

Instant On Fast 1st Copy Speed of 4 Seconds Low Power Requirement (115V, 8A) Operator Replaceable ZnO Master

PRODUCT LIMITATIONS

Single Cassette 250 Sheets 1-20 Quantity Dial Maximum Paper Size 8½ × 14 Variable Exposure Dial Requires Experimentation to Attain Acceptable Copy Quality Cold Pressure Fusing Requires Special Paper to Obtain Optimum Quality

COMPANY: F MODEL: 5 SUGGESTED RETAIL PRICE: \$ RENTAL PRICING: \$			EY BOWES
Price Plan	Monthly Min.	Copies Included	Copy Charge
Annual	\$ 120.00	1-1,000	None

1,001 +

(Purchased Units Only):

Min. Charge	Copies Included	Copy Charge -
\$ 32/mo.	1,500/ma.` 1,501 +	None \$.0080

\$.027

TOSHIBAAMERICA

Competitive Product Guide

TT

PITNEY BOWES 5200

Copier Type: Platen: Segment: Warm Up Time: First/Multi Time:

Photoconductor Type: Exposure Method: Development Method: Drum Cleaning System: Image Fusing System:

Paper Supply: Manual Sheet-Bypass: Capacity: Paper Size Selector: Min/Max Copy Sizes:

Multi-Copy: Exposure Control: Toner Density: Print, Stop Print: Other:

Paper Supply Indicator: Toner Supply Indicator: Number Copies Made / Remaining: Paper Jam / Other Problems: Other:

Mfr.'s Recommended Monthly Volume: Dimensions (H × W × D): Weight: Power Consumption: Moving 1 Instant On Less Than 5 sec., 15 c/m

Zinc Oxide Belt Halogen Lamp Dry Toner Magnetic Brush Cold Pressure

Single Cassette Sheet Fed None 250 Sheets/Cassette Cassette Change Required 8½ × .11 8½ × 14

1-20 Dial, Auto Reset Light/Dark Dial None Print None

None None

1–20, Countdown Dial None None

 $\begin{array}{l} 1000 \ \text{to} \ 8000 \\ 131/_2 \ \times \ 223/_4 \ \times \ 191/_2 \\ 135 \ \text{lbs} \\ 115V, \ 60\text{Hz}, \ 8\text{A} \end{array}$

TOSHIBAAMERICA