

MINOLTA 320

PRODUCT STRENGTHS

Edge to Edge Copy
Electronic Self-diagnostics
Fiberoptics
Clamshell Design
Built-in Dehumidifier
11" x 17" Copy
Sharp Black Peak Image Density Capability

PRODUCT LIMITATIONS

Single Cassette
Moving Platen
Too Frequent Addition of Fuser Oil
Copy Quality Fall-off
Sub Par Drum Cleaning/Recycling System Compared to 530R

COMPANY:	MINOLTA CORPORATION
MODEL:	EP 320
SUGGESTED LIST PRICE:	\$3995
RENTAL PRICING:	Dealer Option
MAINTENANCE CONTRACT (Purchased Units Only):	Dealer Option

TOSHIBA AMERICA

Competitive Product Guide

MINOLTA 320

Copier Type:	TT
Platen:	Moving
Segment:	1
Warm Up Time:	1.5 min.
First/Multi Time:	7 sec./18 c/m
Photoconductor Type:	Seamless Cadmium Sulfide Drum
Exposure Method:	Focused Fiber Optics (Halogen Lamp)
Drum Cleaning System:	Dual Wiper Blades with Toner Recovery
Image Fusing System:	Heat and Pressure
Paper Supply:	Single Cassette Sheet Feed
Manual Sheet-Bypass:	Built-in
Capacity:	250
Paper Size Selector:	None
Min/Max Copy Sizes:	4" x 6" to 11" x 17"
Multi-Copy:	Digital 1-99, Countdown Resets and Returns to 1 in 20 sec.
Exposure Control:	Variable exposure keys
Toner Density:	Automatic Control (Adjustable by Service Technician)
Print, Stop Print:	Print, Clear, Interrupt/Pause
Other:	
Paper Supply Indicator:	Int'l Symbol
Toner Supply Indicator:	Int'l Symbol
Number Copies Made/Remaining:	Multi-copy select and countdown
Paper Jam/Other Problems:	Paper Misfeed Int'l Symbol
Other:	Call Serviceman Int'l Symbol
	Self-diagnostics
	Toner/developing system:
	Microtoning with Recycle
Mfr's Recommended Monthly Volume:	2,000 to 10,000
Dimensions (H x W x D):	21 1/2" x 12 1/4" x 22 1/2"
Weight:	135 lbs.
Power Consumption:	115V, 60Hz, .7KW Max.

TOSHIBA AMERICA