IBM SERIES III MODEL 40

1

PRODUCT STRENGTHS

Reduction 26% to 35% Standard SADF; Optional 20-Bin Sorter

PRODUCT LIMITATIONS

Floor Console, 1450 lbs. Very Large Operating Space 10 Minute Warm-up Time Limited Copy Size

COMPANY: MODEL:

SUGGESTED LIST PRICE:

RENTAL PRICING: MAINTENANCE CONTRACT: IBM Series III Model 40 \$26,460 (Direct Sales) N/A N/A

12/82

Competitive Product Guide

IBM SERIES III MODEL 40

Copier Type: Platen: Segment: Warm Up Time: First/Multi Time:

Photoconductor Type: Exposure Method: Development Method: Drum Cleaning System: Image Fusing System:

Paper Supply: Manual Sheet-Bypass: Capacity: Paper Size Selector: Min/Max Copy Sizes:

Multi-Copy: Exposure Control: Toner Density: Print, Stop Print: Other: Console Fixed 4 10 Minutes 4.5 Seconds/70 CPM

OPC Belt Halogen Lamp Dry Dual Component Blade Heat and Pressure

Dual Trays None 2100/600 Sheets Select Key 8" x 10"/8.5" x 14"

1–999 Light and Dark Keys N/A Print, Collate, Separate Keys Reduction and Duplexing Keys

Paper Supply Indicator: Yes Toner Supply Indicator: Yes Number Copies Made/Remaining: Copies Made and Selected Paper Jam/Other Problems: Check Paper Path Other: Job Recovery

Mfr's Recommended Monthly Volume: Dimensions (H x W x D): Weight: Power Consumption:

30,000 to 75,000 461/2" x 471/2" x 291/2" 1450 lbs. 115 VAC; 60 HZ; 30A

IBM SERIES III MODEL 30

÷

PRODUCT STRENGTHS

Fast Copy Speed Large Paper Reserve Duplexing

PRODUCT LIMITATIONS

Floor Console, 1350 lbs. Very Large Operating Space 10 Minute Warm-up Time Limited Copy Size

фr

COMPANY: MODEL:

د

SUGGESTED LIST PRICE:

RENTAL PRICING: MAINTENANCE CONTRACT: IBM Series III Model 30 \$24,830 (Direct Sales) N/A N/A

12/82

Competitive Product Guide

IBM SERIES III MODEL 30

Copier Type: Platen: Segment: Warm Up Time: First/Multi Time:

Photoconductor Type: Exposure Method: Development Method: Drum Cleaning System: Image Fusing System:

Paper Supply: Manual Sheet-Bypass: Capacity: Paper Size Selector: Min/Max Copy Sizes:

Multi-Copy: Exposure Control: Toner Density: Print, Stop Print: Other: Console Fixed 4 10 Minutes 4 5 Seconds/70 CPM

OPC Belt Halogen Lamp Dry Dual Component Blade Heat and Pressure

Dual Trays None 2100/600 Sheets Select Key 8" x 10"/8.5" x 14"

1–999 Light/Dark Keys N/A Print, Collate, Separate Keys Duplexing Button

Paper Supply Indicator: Yes Toner Supply Indicator: Yes Number Copies Made/Remaining: Copies Made and Selected Paper Jam/Other Problems: Check Paper Path Other: Job Recovery

Mfr's Recommended Manthly Volume: Dimensions (H x W x D): Weight: Power Consumption:

30,000 to 75,000 461/2" x 421/4" x 291/2" 1350 lbs. 115 VAC; 60 HZ; 30 A