CANON NP-5500

PRODUCT STRENGTHS

Variable Thruput Oversize Capability (11 × 17) Two Reduction Modes (25%, 36%) Push Button Copy Size Change

PRODUCT LIMITATIONS

High Cost Large Size-Space Requirements Inconvenient Paper Tray Access Blind to Yellows (CdS Drum) Requires Dedicated 20A Line Manual Reset of Copy Quantity Dial

COMPANY: MODEL: SUGGESTED RETAIL PRICE: RENTAL PRICING:

MAINTENANCE CONTRACT (Purchased Units Only): CANON NP-5500 \$10,495 Dealer Option

Dealer Option

TOSHIBAAMERICA

Competitive Product Guide

CANON NP-5500

Copier Type:

Platen: Segment:

Warm Up Time: First/Multi Time:

Photoconductor Type:

Exposure Method: Development Method: Drum Cleaning System: Image Fusing System:

Paper Supply: Manual Sheet-Bypass:

Capacity: Paper Size Selector: Min/Max Copy Sizes:

Multi-Copy: Exposure Control: Toner Density:

Print, Stop Print:

Other:

Paper Supply Indicator: Toner Supply Indicator: Number Copies Made/

Remaining:

Paper Jam/Other Problems: Other:

Mfr.'s Recommended Monthly

Volume: Dimensions (H \times W \times D):

Weight: Power Consumption: Console

Stationary Flatbed

31/2 min.

6½ sec/26 c/m (regular) 13 c/m (reduction)

Cadmium Sulfide Drum Halogen Lamp Dry Toner

Blade, Toner Recovery Hot Pressure Roller

Dual Cassette Sheet-Fed None

250 Sheets/Cassette Cassette buttons 5½ × 8½

 11×17

1-99 Manual Reset Exposure Dial

Automatic Toner Replenisher

Multi Copy & Single Copy Copy Stop Button Control Counter

Check, Cassette Display Check Replenisher Display

LED Display, Copy Count-up Check Paper Feed Display Paper Size Selected, Reduction Indicator, Cassette Size Selected

8,000 to 40,000

 $36\frac{1}{2} \times 327/8 \times 24\frac{1}{2}$

485 lbs. 120V, 60Hz, 15A

TOSHIBAAMERICA