

# **CANON NP-30**

## **PRODUCT STRENGTHS**

Instant On  
Quantity Selector 1-20 + Continuous  
Flexible Thruput  
Microprocessor  
Standard Outlet

## **PRODUCT LIMITATIONS**

Liquid Toner—(Flammable-Kerosene Based)  
Special Paper Required  
No Illuminated LED Quantity Indicator  
No Stop/Clear Button  
No Pause Button

<b>COMPANY:</b>	<b>CANON</b>
<b>MODEL:</b>	<b>NP-30</b>
<b>SUGGESTED RETAIL PRICE:</b>	<b>\$2,695</b>
<b>RENTAL PRICING:</b>	<b>Dealer Option</b>
<b>MAINTENANCE CONTRACT</b> (Purchased Units Only):	<b>Dealer Option</b>

**TOSHIBA AMERICA**

# Competitive Product Guide

## CANON NP-30

Copier Type:	TT
Platen:	Moving
Segment:	1
Warm Up Time:	Instant
First/Multi Time:	12 sec./12 c/m
Photoconductor Type:	Seamless Cadmium Sulfide Drum
Exposure Method:	Fluorescent Lamp
Development Method:	Liquid Toner
Drum Cleaning System:	Blade
Image Fusing System:	Contact Heater Plate, Toner Recovery
Paper Supply:	Single Cassette Sheet-Fed
Manual Sheet-Bypass:	None
Capacity:	200 Sheets/Cassette
Paper Size Selector:	Cassette Change Required
Min/Max Copy Sizes:	5 1/2 x 8 1/2 10 1/8 x 14 3/8
Multi-Copy:	1-20 M, Auto Reset Dial
Exposure Control:	Exposure Control Lever
Toner Density:	Automatic Toner Replenisher System
Print, Stop Print:	Copy Stop
Other:	None
Paper Supply Indicator:	Indicator (int'l symbol)
Toner Supply Indicator:	Indicator (int'l symbol)
Number Copies Made/ Remaining:	None
Paper Jam/Other Problems:	Paper Jam Indicator (int'l symbol)
Other:	Developer Supply Indicator (int'l symbol)
Mfr.'s Recommended Monthly Volume:	0 To 5,000
Dimensions (H x W x D):	11 13/16 x 25 13/16 x 20
Weight:	139 lbs.
Power Consumption:	120V, 60Hz, 15A

# TOSHIBA AMERICA