

SHARP SF 770

PRODUCT STRENGTHS

Clamshell Design (straight paper path)
Self-diagnostic Codes Identifies 25 Malfunction Points
Copies ALL Colors. Is Panchromatic
Minimum Copy Quality Fall-off Between PMs
Excellent Copies from Both Photos and Halftones
Automatic Toning
Biodegradable Photoconductor

PRODUCT LIMITATIONS

Copy Edge Void
Photoconductor System Untried
Single Cassette
Slow

COMPANY:

SHARP
ELECTRONICS
SF 770

MODEL:

SUGGESTED LIST PRICE:

\$3695

RENTAL PRICING:

Dealer Option

MAINTENANCE CONTRACT

(Purchased Units Only):

Dealer Option

TOSHIBA AMERICA

Competitive Product Guide

SHARP SF 770

Copier Type:	TT
Platen:	Stationary
Segment:	2
Warm Up Time:	2 min.
First/Multi Time:	6.5 sec./15 c/m
Photoconductor Type:	OPC (organic photoconductor) Master
Exposure Method:	Halogen Lamp
Drum Cleaning System:	Reverse Charge (polarity) Plus Magnetic Brush (roller)
Image Fusing System:	Heat and Pressure Rollers
Paper Supply:	Single Cassette
Manual Sheet-Bypass:	Manual By-pass Sheet Guide
Capacity:	250
Paper Size Selector:	None
Min/Max Copy Sizes:	5 1/2" x 8 1/2" to 11" x 17"
Multi-Copy:	1-99 Auto-countdown with Repeat/Pause. Returns to Std. Mode in 2 min.
Exposure Control:	Horizontal Lever (1-5 scale)
Toner Density:	AutoToning—No Operator Adjustment/ Service Technician Adjustment
Print, Stop Print:	Print/Ready and Clear (stop) Buttons
Other:	
Paper Supply Indicator:	Int'l Symbol
Toner Supply Indicator:	Int'l Symbol
Number Copies Made/Remaining:	Countdown (copies made readout)
Paper Jam/Other Problems:	Int'l Symbols: "Misfeed" and "Call Service Technician"
Other:	Master Change Indicator Self-diagnostic (zero/readout key) Via 25 Codes Which Identify Malfunction Toner/Developing System: Dual Component PM Cycle: 10,000 copies. Standard Dehumidifier
Mfr's Recommended Monthly Volume:	5,000 to 10,000
Dimensions (H x W x D):	16 3/4" x 25 1/2" x 21 1/4"
Weight:	143 lbs.
Power Consumption:	1.4KW Max.

TOSHIBA AMERICA